


# MONOCOLO C90 0-10V 110V


ver. 20200404\_Rev\_0

year: 2018  
code: 2250210A20000  
type: ceiling lamp  
application: indoor



### Technical drawing

Size ref. image mm - inch



### Technical data

Light source	LED
Circuit structure	COB LED G7
Light emission direction	direct
Power	16 W
Source lumens	2914 lm
Source efficacy	187 lm/W
Energy class	A
Delivered lumens	1654 lm
Secondary	500mA
Colour temperature	3000 K / variants page 2
Colour rendering index	80 CRI / variants page 2
Standard Deviation of Colour Matching	3 SDCM
Safety class	I
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	●
Operating temperature	+10° / +40°
CE	●
UL	○

### Optional

Emergency mode	○
Motion sensor	○
Directional	○

### Packing

Net weight	1.1 Kg
Packaging 1	Ø100 x 330 mm / 1.5 kg
Packaging 2	
Packaging 3	
Packaging 4	
Packaging 5	

### Structure

Material	aluminium
Finish	embossed white / variants page 2

### Diffuser

Material	polycarbonate
Finish	opal / variants page 2

### Electronics / Driver

Included	Yes
Quantity	1
Voltage	100-277V 50/60 Hz

### Dimmable



### Hanging cables

Stainless steel cables standard length (custom available)	○
Electric cable standard length (custom available)	-

### Warranty

Duration	2 years
----------	---------


# MONOCOLO C90 0-10V 110V

ver. 20200404\_Rev\_0


year: **2018**  
code: **2250210A20000**  
type: **ceiling lamp**  
application: **indoor**

## Available variants


### Colour temperature




### Colour rendering index



### Structure finish



### Diffuser / Optical



# MONOCOLO C90 0-10V 110V

ver. 20200404\_Rev\_0


year: **2018**  
code: **2250210A20000**  
type: **ceiling lamp**  
application: **indoor**

Lighting features	
Source lumens	2914 lm
Source efficacy	187 lm/W
Consumption	19 W
Delivered lumens	1654 lm
Luminaire efficacy	86 lm/W
Secondary voltage	500mA
Colour temperature	3000 K / variants page 2
Colour rendering index	Array
Standard Deviation of Colour Matching	3 SDCM

LED life / Failure ratio	
LED life cycle	50000 h

UGR	
X=4H / Y=8H	
Reflection factor	
UGR transversal	
UGR axial	

## Photometric 1



## Photometric 2

